1. COMPANY IDENTIFICATION

Microlon, Inc

ADDITIVES

INCLUDING THE FOLLOWING:

STEL - Short Term Exposure Limit

RQ - Reportable Quantity

A1-5 - Appendix A Categories

POTENTIAL HEALTH EFFECTS

from similar materials.

3. HAZARDS IDENTIFICATION

C - Ceiling Limit

CALCIUM HYDROXIDE

Austin, TX 78705

2520 Longview St., Suite 313

MSDS Requests: (800) 962-4152

100% MICROLON HIGH TEMP GREASE The percentage compositions are given to allow for the various ranges of the components present in the whole product and may not equal 100%. Components Amount Limit/Qty Agency/Type LUBRICATING BASE OIL: Severly Refined Petroleum Distillate

	> 60%	5 mg/m3	ACGIH TWA
		10 mg/m3	ACGIH STEL
		5 mg/m3	OSHA PEL
The BASE OIL may be a	nixtue of any	of the following	ng: CAS 64741
CAS 64742014, CAS 64	742525. CAS	64742536. C	CAS 64742547.

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS 1305620 20% 5 mg/m3 **ACGIH TWA OSHA PEL** 5 mg/m3

<20%

COMPOSITION COMMENT: All th ecomponents of this material are on the Toxic Substances Control Act Chemical Substance Inventory. This product fits the ACGIH

definition fo rmineral oil mist.

The ACGIH TLV is 5 mg/m3, the OSHA PEL is 5 mg/m3.

TLV - Threshold Limit Value	

EYE: This substance is not expected to cause prolonged or significant eye irritation.

organs if swallowed. This hazard evaluation is based on data from similar materials.

organs if inhaled. This hazard evaluation is based on data from similar materials.

SKIN: This substance is not expected to cause prolonged or significant skin irritation. The systemic toxicity of this substance has not been determined. However, it should be practically non toxic to internal organs if it gets on the skin. The hazard evaluation is based on data

INGESTION: The systemic toxicity of this substance has not been determined. However, it should be practically non toxic to internal

INHALATION: The systemic toxicity of this substance has not been determined. However, it should be practically non toxic to internal

TWA - Time Weighted Average

TPQ - Threshold Planning Quantity

CAS - Chemical Abstract Service Number

PEL - Permissible Exposure Limit

() - Change Has Been Proposed

CAS 64742627, CAS 64742650 or CAS 72623837.

24 hr Emergency: Chemtrec (800) 424-9300

EYE: No first aid procedures are required. However, as a precaution, flush eyes with fresh water for 15 minutes. Remove contact lenses if worn. SKIN: No first aid procedures are required. As a precaution, wash skin thoroughly with soap and water. Remove and wash contaminated

INGESTION: If swallowed, give water or milk to drink and telephone for medical advice. Consult medical personnel before inducing vomiting. If medical advice cannot be obtained, then take the person and product container to the neareast medical emergency treatment

INHALATION: Since this material is not expected to be an immediate inhalation problem, no first aid procedures are required.

FLAMMABLE PROPERTIES FLASH POINT (COC): 392°F (195° C) Min **AUTOIGNITION: NDA** FLAMMABILITY LIMITS: (% by volume in air): Lower: NA Upper: NA

EXTINGUISHING MEDIA: CO2, Dry Chemical, Foam, Water Fog

NFPA RATINGS: Health 1; Flammability 1; Reactivity 0.

(Least-0, Slight-1, Moderate-2, High-3, Extreme-4). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or The National Paint and Coating Association (for HMIS ratings).

FIRE FIGHTING INSTRUCTIONS: For firest involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

COMBUSTION PRODUCTS: Normal combustion forms carbon dioxide, water vapor and may produce oxides of sulfur, nitrogen and phosphorous. Incomplete combustion can produce carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES This material is not expected to cause any environmental problems other than those associated with oil spills.

Clean up spills immediately.

4. FIRST AID MEASURES

5. FIRE FIGHTING MEASURES

clothing.

center or hospital.

7. HANDLING AND STORAGE

CAUTION - DO NOT use pressure to empty drum or drum may rupture with explosive force. DO NOT weld, heat or drill container.

Residue may ignite with explosive violence if heated sufficiently.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT EYE/FACE PROTECTION: No special eye protection is usually necessary.

SKIN PROTECTION: No special skin protection is usually necessary. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing protective clothing.

RESPIRATORY PROTECTION: No special respiratory protection is normally required. ENGINEERING CONTROLS: No special ventilation is necessary.

NA EVAPORATION RATE: NA PERCENT VOLATILE (VOL): 10. STABILITY AND REACTIVITY HAZARDOUS DECOMPOSITION PRODUCTS: NDA CHEMICAL STABILITY: Stable CONDITION TO AVOID: NDA INCOMPATIBILITY WITH OTHER MATERIALS: May react with strong oxidizing agents, such as chlorates, nitrates, peroxides, etc. HAZARDOUS POLYMERIZATION: Polymerization will not occur. 11. TOXICOLOGICAL INFORMATION EYE EFFECTS: No product toxicology data available. The hazard evaluation was based on data from similar materials. SKIN EFFECTS: No product toxicology data available. The hazard evaluation was based on data from similar materials. ACUTE ORAL EFFECTS: No product toxicology data available. The hazard evaluation was based on data from similar materials. ACUTE INHALATION EFFECTS: No product toxicology data available. The hazard evaluation was based on data from similar materials.

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic to humans (Group 1), probably carcinogenic

Dark Green Grease

1.08 @ 20/20C

Soluble in hydrocarbon solvents; insoluble in water.

NDA

NA

NA

NA

NDA NDA

NDA

ECOTOXICITY: NDA

12. ECOLOGICAL INFORMATION

ADDITIONAL TOXICOLOGY INFORMATION:

to humans (Groups 2A), or possibly carcinogenic to humans (Group 2B).

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DESCRIPTION:

VAPOR DENSITY (AIR=1)

VAPOR PRESSURE:

BOILING POINT:

FREEZING POINT:

MELTING POINT: SOLUBILITY:

SPECIFIC GRAVITY:

DENSITY:

рΗ

13. DISPOSAL CONSIDERATIONS

Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental or health authorities for approved disposal of this material.

ENVIRONMENTAL FATE: This material is not expected to present any environmental problems other than those associated with oil spills.

14. TRANSPORT INFORMATION

The description shown may not apply to all shipping situations.

Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and

mode specific or quantity specific shipping requirements.

DOT SHIPPING NAME:	NOT DESIGNATED AS A HAZARDOUS MATERIAL BY THE FEDERAL DOT	
DOT HAZARD CLASS:	NOT APPLICABLE	
DOT IDENTIFICACTION NUMBER:	NOT APPLICABLE	
DOT PACKING GROUP:	NOT APPLICABLE	

15. REGULATORY INFORMATION

SARA 311	1. Immediate (Acute) Health Effects:	NO	
CATEGORIES	2. Delayed (Chronic) Health Effects:	МО	
	3. Fire Hazard:	NO	
	4. Sudden Release of Pressure Hazard:	NO	
	5. Reactivity Hazard:	NO	

REGULATORY LISTS SEARCHED:

11 = NJ RTK	21 = TSCA Sect 4(e)
12 = CERCLA 302.4	22 = TSCA Section 5(a) (e) (f)
13 = MN RTK	23 = TSCA Sect 6
14 = ACGIH TWA	24 = TSCA Sect 12(b)
15 = ACGIH STEL	25 = TSCA Sect 8(a)
16 = ACGIH Calc TLV	26 = TSCA Sect 8(d)
17 = OSHA PEL	
18 = DOT Marine Pollutant	28 = CANADIAN WHMIS
19 = Chevron TWA	29 = OSHA CEILING
20 = EPA Carcinogen	30 = Chevron STEL
	12 = CERCLA 302.4 13 = MN RTK 14 = ACGIH TWA 15 = ACGIH STEL 16 = ACGIH Calc TLV 17 = OSHA PEL 18 = DOT Marine Pollutant 19 = Chevron TWA

The following components of this material are found on the regulatory lists indicated.

SEVERELY REFINED PETROLEUM DISTILLATE is found on lists: 14, 15, 17.

16. OTHER INFORMATION

REVISION STATEMENT: This Material Safety Data Sheet has been revised to comply with the ANSI Z400.1 Standard. Changes have also been made throughout this Material Safety Data Sheet. Please read the entire document.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.